



FOREST LIGHTING

Sustainable illumination



6" LED Downlights



Dimmable

Forest lighting 6 inch downlight installs in standard downlight housings and is perfect for indoor general lighting in residential, office and hospitality applications. Its Color Rendering Index of 90 makes colors more vibrant and richer in the environment it illuminates. By providing over 1050lm while consuming only 15W, it replaces 90W incandescent lamps and saves tremendous amount of energy.

FEATURES & BENEFITS

- Installs in standard down light housings
- Easy and quick to install
- Rated lifetime of 35,000 Hrs



WARRANTY

5 Year Warranty



DOWNLIGHT MODELS

MODEL NO.	RECESSED HOUSING SIZE	INPUT POWER (W)	CCT	DELIVERED LIGHT OUTPUT (LM)
DL-6-15W30KDH-L8-LS	6 in	15	3000K	1050
DL-6-15W40KDH-L8-LS	6 in	15	4000K	1050
DL-6-15W50KDH-L8-LS	6 in	15	5000K	1050


LISTINGS AND CERTIFICATIONS



LED Downlights

SPECIFICATION INFORMATION

Input Power	15W
Input Voltage	120V / 60Hz
Base Type	E26
Correlated Color Temperature (CCT)	3000K, 4000K, 5000K
Color Rendering Index	>90
Luminous Flux	1050 lm
Efficacy	70lm/W
Beam Angle	120°




ORDERING INFORMATION

Example: DL-6-15W30KDH-L8-LS

Model	Size	Input Power	CCT	DH-L8-LS
DL	6 6"	15W 15W	30K 3000K	
			40K 4000K	
			50K 5000K	

LED Downlights

PHOTOMETRY



Curve 1: 0 degree
Curve 2: 90 degree

Performance Data

Delivered Lumens (lms)	1112
Input Wattage (W)	14.76
Efficacy (LpW)	75.0
Voltage (V)	120

Zonal Lumen Summary

Zone	Lumens	% of Fixture
0-30	394.28	35.40
0-40	629.91	56.60
0-60	996.76	89.60
0-90	1111.22	99.90
40-70	447.76	40.30
60-80	109.25	9.80
0-180	1112.28	100.00